

Civil Engineering Department

University of Engineering and Technology, Lahore. Pakistan Landline: 042-99029245 & 042-99029202 Mobile: 0307-0496895



2427 Engr. Ubaid

Test Specification

To: **Director Projects**

Innovative ® Construction Company, Lahore

Project: Construction of ABL Branch at Jubilee Town, Lahore

| Our Ref. No. CL/0 | CED/ 6670 | Dated: | 17-12-21 |
|-------------------|--------------------|--------|----------|
| Your Ref. No. | ICL/ABL/JT/1221/01 | Dated: | 12-12-21 |

COMPRESSION TEST REPORT



Concrete Cubes/Concrete Cylinders/Bricks/Cores/Tuff Tiles/Pavers

16-12-21 in dry/wet condition Specimens received on: 13-12-21 Tested on:

| Sr. No. | Mark* | | - | Date* YYYY | Size (in) | Wet Weight (Kg/ gms) | Dry Weight (Kg/ gms) | Area of X-Section (Sq. in) | Ultimate load (Imp.Tons) | Ultimate Stress (psi) | Water Absorpti on (%) | Remarks |
|---------|-------|---|----|---------------|--------------|----------------------------|----------------------------|----------------------------------|--------------------------------|-----------------------------|-----------------------------|--------------|
| 1 | | 3 | 12 | 2021 | 6Diax12 | | 13 | 28.28 | 45 | 3564 | | Non Engraved |
| 2 | | 3 | 12 | 2021 | 6Diax12 | | 13 | 28.28 | 38 | 3010 | | Non Engraved |
| 3 | | 3 | 12 | 2021 | 6Diax12 | | 13.4 | 28.28 | 37 | 2931 | | Non Engraved |
| 4 | | | | | | | | | | | | |
| 5 | | | | | | | | | | | | |
| 6 | | - | 1 | 1 | | | | | | | | |
| 7 | | | | | | | | | | | | |
| 8 | | - | - | - | | | | | | | | |
| 9 | | | - | | | | | | | | | |
| 10 | | - | - | - | | | | | | | | |
| 11 | | - | - | 1 | | | | | | | | |
| 12 | | | | | | | | | | | | |
| 13 | | | | | | | | | | | | |
| 14 | | | | | | | | | | | | |
| 15 | | | | - | | | | | | | | |
| 16 | | | | | | | | | | | | |

Witnessed by: Nil

Results can also be seen on website https://civil.uet.edu.pk/concrete-laboratory-reports1/

1. * as engraved on the specimens (if any)

2. ** BS3921 requires average of ten clay brick samples for crushing strength and water absorption

*** BS5328 requires mean of two cube sample strength at 28 days as characteristic strength
**** ACI318-08 requires mean of two sample (6"diax12" cylinder) strength at 28 days as compressive strength

Note: Above results pertain to the unsealed samples supplied to the laboratory

1. The laboratory is not responsible for sampling, originality and construction conditions (such as mix proportion, w/c ratio, compaction, curing and quality of ingredients) 2. The test results are recommended to be interpreted in the light of above factors by the engineer.



Civil Engineering Department

University of Engineering and Technology, Lahore. Pakistan Landline: 042-99029245 & 042-99029202 Mobile: 0307-0496895



2429 Engr. Ubaid

Test Specification

To: Mr. Tahir Nazir Bhatti (Project Manager)

IKAN Engineering Services (Pvt.) Ltd. Lahore

Project: Relocation of Jotun Manufacturing Facility to Sunder Estate (C-120 Footings / C-110 Substructure Columns)

Dated:

Dated:

17-12-21

13-12-21

Our Ref. No. CL/CED/ 6671

Your Ref. No. IKAN/CW138/PM/002

COMPRESSION TEST REPORT



Concrete Cubes/Concrete Cylinders/Bricks/Cores/Tuff Tiles/Pavers

Specimens received on: 14-12-21 Tested on: 16-12-21 in dry/wet condition

| | | - | | | | | | | | | | 1 |
|---------------|------------------|---------------|----|-------|---------|---------------|---------------|----------------------|------------|--------------------|-------------------|--------------|
| Sr. No. | Sr. No. Mark* | Casting Date* | | Date* | Size | Wet Weight | Dry Weight | Area of X-Section | | Ultimate Stress | Water Absorpti | Remarks |
| | | DD | мм | YYYY | (in) | (Kg/ gms) | (Kg/ gms) | (Sq. in) | (Imp.Tons) | (psi) | on (%) | |
| 1 | | 13 | 11 | 2021 | 6Diax12 | | 13.6 | 28.28 | 59 | 4673 | | Non Engraved |
| 2 | | 13 | 11 | 2021 | 6Diax12 | | 13.2 | 28.28 | 51 | 4040 | | Non Engraved |
| 3 | | 13 | 11 | 2021 | 6Diax12 | | 14 | 28.28 | 66 | 5228 | | Non Engraved |
| 4 | | | - | | | | | | | | | |
| 5 | | | - | | | | | | | | | |
| 6 | | | 1 | | | | | | | | | |
| 7 | | | - | | | | | | | | | |
| 8 | | | - | | | | | | | | | |
| 9 | | | - | | | | | | | | | |
| 10 | | | - | | | | | | | | | |
| 11 | | | | | | | | | | | | |
| 12 | | | - | | | | | | | | | |
| 13 | | | | | | | | | | | | |
| 14 | | | | | | | | | | | | |
| 15 | | | | | | | | | | | | |
| 16 | | | | | | | | | | | | |
| VAC AND A A A | Midenand by: Nil | | | | | | | | | | | |

Witnessed by: Nil

Results can also be seen on website https://civil.uet.edu.pk/concrete-laboratory-reports1/

1. * as engraved on the specimens (if any)

2. ** BS3921 requires average of ten clay brick samples for crushing strength and water absorption

*** BS5328 requires mean of two cube sample strength at 28 days as characteristic strength
**** ACI318-08 requires mean of two sample (6"diax12" cylinder) strength at 28 days as compressive strength

Note: Above results pertain to the unsealed samples supplied to the laboratory

1. The laboratory is not responsible for sampling, originality and construction conditions (such as mix proportion, w/c ratio, compaction, curing and quality of ingredients) 2. The test results are recommended to be interpreted in the light of above factors by the engineer.

Supervisor (Lab)



Civil Engineering Department

University of Engineering and Technology, Lahore. Pakistan Landline: 042-99029245 & 042-99029202 Mobile: 0307-0496895



2433 Engr. Ubaid

Test Specification

To: Mr. Nouman Rafique (Chief Technical Officer) Sabcon Associates (Pvt.) Ltd. Lahore

Project: Construction of Commercial Building a 51A Gulberg III, Lahore

| Our Ref. No. CL/C | CED/ 6672 | Dated: | 17-12-21 |
|-------------------|--------------------|--------|----------|
| Your Ref. No. | SABCON/2021/CTO/02 | Dated: | 14-12-21 |

COMPRESSION TEST REPORT



Concrete Cubes/Concrete Cylinders/Bricks/Cores/Tuff Tiles/Pavers

Specimens received on: 14-12-21 Tested on: 16-12-21 in dry/wet condition

| Sr. No. | Mark* | | - | Date* YYYY | Size (in) | Wet Weight (Kg/ gms) | Dry Weight (Kg/ gms) | Area of X-Section (Sq. in) | | Ultimate Stress (psi) | Water Absorpti on (%) | Remarks |
|---------|-------|----|----|---------------|--------------|----------------------------|----------------------------|----------------------------------|----|-----------------------------|-----------------------------|----------|
| 1 | | 17 | 11 | 2021 | 6Diax12 | | 13.2 | 28.28 | 26 | 2059 | | Engraved |
| 2 | | 17 | 11 | 2021 | 6Diax12 | | 13.4 | 28.28 | 23 | 1822 | | Engraved |
| 3 | | | | | | | | | | | | |
| 4 | | | | | | | | | | | | |
| 5 | | | - | | | | | | | | | |
| 6 | | | - | | | | | | | | | |
| 7 | | | | | | | | | | | | |
| 8 | | | - | | | | | | | | | |
| 9 | | | - | | | | | | | | | |
| 10 | | | - | | | | | | | | | |
| 11 | | - | - | | | | | | | | | |
| 12 | | | | | | | | | | | | |
| 13 | | | | | | | | | | | | |
| 14 | | | | | | | | | - | | | |
| 15 | | | | | | | | | - | | | |
| 16 | | | | | | | | | | | | |

Witnessed by: Nil

Results can also be seen on website https://civil.uet.edu.pk/concrete-laboratory-reports1/

1. * as engraved on the specimens (if any)

2. ** BS3921 requires average of ten clay brick samples for crushing strength and water absorption

*** BS5328 requires mean of two cube sample strength at 28 days as characteristic strength
**** ACI318-08 requires mean of two sample (6"diax12" cylinder) strength at 28 days as compressive strength

Note: Above results pertain to the unsealed samples supplied to the laboratory

1. The laboratory is not responsible for sampling, originality and construction conditions (such as mix proportion, w/c ratio, compaction, curing and quality of ingredients) 2. The test results are recommended to be interpreted in the light of above factors by the engineer.

Supervisor (Lab)



Civil Engineering Department

University of Engineering and Technology, Lahore. Pakistan Landline: 042-99029245 & 042-99029202 Mobile: 0307-0496895



2437 Engr. Ubaid

Test Specification

To: Mr. Muhammad Azeem (Operation Manager)

Amer Adnan Associates, # 17-E-II, Gulberg III, Lahore

Project: Hotel Building at 24-A Block E/2 at Gulberg III, Lahore

| Our Ref. No. CL/ | CED/ 6673 | Dated: | 17-12-21 |
|------------------|--------------|--------|----------|
| Your Ref. No. | AAA/24A/0068 | Dated: | 14-12-21 |

COMPRESSION TEST REPORT



Concrete Cubes/Concrete Cylinders/Bricks/Cores/Tuff Tiles/Pavers

Specimens received on: 15-12-21 Tested on: 16-12-21 in dry/wet condition

| Sr. No. | Mark* | | - | Date* YYYY | Size (in) | Wet Weight (Kg/ gms) | Dry Weight (Kg/ gms) | Area of X-Section (Sq. in) | Ultimate Ioad (Imp.Tons) | | Water Absorpti on (%) | Remarks |
|---------|----------|----|----|---------------|--------------|----------------------------|----------------------------|----------------------------------|--------------------------------|------|-----------------------------|----------|
| 1 | 5000 Psi | 16 | 11 | 2021 | 6Diax12 | | 14 | 28.28 | 55 | 4356 | | Engraved |
| 2 | 5000 Psi | 16 | 11 | 2021 | 6Diax12 | | 14 | 28.28 | 57 | 4515 | | Engraved |
| 3 | | | | | | | | | | | | |
| 4 | | | | | | | | | | | | |
| 5 | | | | | | | | | | | | |
| 6 | | | | | | | | | | | | |
| 7 | | | | | | | | | | | | |
| 8 | | | | | | | | | | | | |
| 9 | | | | | | | | | | | | |
| 10 | | | - | | | | | | | | | |
| 11 | | | | | | | | | | | | |
| 12 | | | | | | | | | | | | |
| 13 | | | | | | | | | | | | |
| 14 | | | | | | | | | | | | |
| 15 | | | | | | | | | | | | |
| 16 | | | | | | | | | | | | |

Witnessed by: Nil

Results can also be seen on website https://civil.uet.edu.pk/concrete-laboratory-reports1/

1. * as engraved on the specimens (if any)

2. ** BS3921 requires average of ten clay brick samples for crushing strength and water absorption

*** BS5328 requires mean of two cube sample strength at 28 days as characteristic strength
**** ACI318-08 requires mean of two sample (6"diax12" cylinder) strength at 28 days as compressive strength

Note: Above results pertain to the unsealed samples supplied to the laboratory

1. The laboratory is not responsible for sampling, originality and construction conditions (such as mix proportion, w/c ratio, compaction, curing and quality of ingredients) 2. The test results are recommended to be interpreted in the light of above factors by the engineer.