

ORIGINAL								
A carbon copy for								
the report has								
been retained in								
the lab for record.								

2475 Dr. Qasim Shaukat

To: (Engr. Khalid Qadeer Mian) Chief Executive. Eastern Construction Co. Model Town Extension, Lahore. Project: Construction of 60 CUM/HR Capacity Waste Water Treatment Plant. (Client; Fauji Fresh n Freeze Limited)

Our Ref. No. CL/	CED/ 6761	Dated:	30-12-21	Test Specification
Your Ref. No.	ECC/UET/FFFL-SWL/2021/43	Dated:	23-12-21	(ASTM C39)

COMPRESSION TEST REPORT



Concrete Cubes/Concrete Cylinders/Bricks/Cores/Tuff Tiles/Pavers

Specim	ens received on:	2	3-12	-21	Tested on:	30-1	2-21	in dry/we	t condition			
Sr. No.	Mark*		-	Date* YYYY	Size (in)	Wet Weight (Kg/ gms)	Dry Weight (Kg/ gms)	Area of X-Section (Sq. in)	Ultimate Ioad (Imp.Tons)	Ultimate Stress (psi)	Water Absorpti on (%)	Remarks
1	Bed Concrete	2	12	2021	6Diax12		14	28.28	71	5624		Non Engraved
2	Bed Concrete	2	12	2021	6Diax12		13.8	28.28	91	7208		Non Engraved
3	Bed Concrete	2	12	2021	6Diax12		14	28.28	71	5624		Non Engraved
4												
5					/	RINE	RIATE	-				
6					>	T READ IN						
7						DHE NHOLE OF THY LORID VIND		EB				
8					ISN /							
9												
10						- (A	INR E					
11												
12												
13												
14												
15												
16												
Witnessed by: Nil												

Results can also be seen on website https://civil.uet.edu.pk/concrete-laboratory-reports1/

1. * as engraved on the specimens (if any)

2. ** BS3921 requires average of ten clay brick samples for crushing strength and water absorption

3. *** BS5328 requires mean of two cube sample strength at 28 days as characteristic strength

4. **** ACI318-08 requires mean of two sample (6"diax12" cylinder) strength at 28 days as comprensive strength

Note: Above results pertain to the unsealed samples supplied to the laboratory

1. The laboratory is not responsible for sampling, originality and construction conditions (such as mix proportion, w/c ratio, compaction, curing and quality of ingredients) 2. The test results are recommended to be interpreted in the light of above factors by the engineer.