

Plain and Reinforced Concrete Laboratory

Civil Engineering Department
University of Engineering and Technology, Lahore. Pakistan

ORIGINAL
A carbon copy for the report has been retained in the lab for record.

1993 Engr. Ubaid

To: Mr. Naeem, Project Manager

Q-Links Property Management Pvt. Ltd.

Project: Broadway Heights-3, Bahria Town, Lahore.

Landline: 042-99029245 & 042-99029202

 Our Ref. No. CL/CED/
 6008
 Dated:
 07-10-21
 Test Specification

 Your Ref. No.
 QLC-BO-BH2-2021-068
 Dated:
 28-09-21
 (ASTM C39)

Mobile: 0307-0496895

COMPRESSION TEST REPORT

Concrete Cubes/Concrete Cylinders/Bricks/Cores/Tuff Tiles/Pavers

Specimens received on: 29-09-21 Tested on: 06-10-21 in dry/wet condition





Sr. No. Mark*		Casting Date*			Size	Wet Weight	Dry Weight	Area of X-Section	Ultimate load	Ultimate Stress	Absorpti	Remarks		
		DD	MM	YYYY	(in)	(Kg/ gms)	(Kg/ gms)	(Sq. in)	(Imp.Tons)	(psi)	on (%)			
1	2nd F. Column 3750Psi	31	8	2021	6Diax12		13.4	28.28	41	3248		Non Engraved		
2	2nd F. Column 3750Psi	31	8	2021	6Diax12		13.4	28.28	45	3564		Non Engraved		
3										-				
4						-	-			-				
5					-	BILLIAM	BARRA							
6					-6	READ IN THE NAME OF THE	7							
7					- Es	فلق « CREATURE فلق								
8					F		0,0							
9					- 40		= ==							
10						ZAHUY								
11														
12														
13														
14														
15														
16														
Witness	ed by:		Witnessed hv:											

Witnessed by:

Results can also be seen on website https://civil.uet.edu.pk/concrete-laboratory-reports1/

- 1. * as engraved on the specimens (if any)
- 2. ** BS3921 requires average of ten clay brick samples for crushing strength and water absorption
- 3. *** BS5328 requires mean of two cube sample strength at 28 days as characteristic strength
- 4. **** ACl318-08 requires mean of two sample (6"diax12" cylinder) strength at 28 days as comprerssive strength

- 1. The laboratory is not responsible for sampling, originality and construction conditions (such as mix proportion, w/c ratio, compaction, curing and quality of ingredients)
- 2. The test results are recommended to be interpreted in the light of above factors by the engineer.



University of Engineering and Technology, Lahore. Pakistan
Landline: 042-99029245 & 042-99029202 Mobile: 0307-0496895

ORIGINAL
A carbon copy for
the report has
been retained in

the lab for record.

2014 Engr. Ubaid

To: Muhammad Azeem (Operation Manager)

Amer Adnan Associates, 17-E-II, Gulberg III, Lahore.

Project: Hotel Building at 24-A Block E/2 at Gulberg III, Lahore.

 Our Ref. No. CL/CED/ 6009
 Dated:
 07-10-21
 Test Specification

 Your Ref. No.
 AAA/ 24A/ 0051
 Dated:
 01-10-21
 (ASTM C39)

COMPRESSION TEST REPORT

Concrete Cubes/Concrete Cylinders/Bricks/Cores/Tuff Tiles/Pavers

Specimens received on: 01-10-21 Tested on: 06-10-21 in dry/wet condition





Sr. No.	Mark*	Casting Date*			Size	Wet Weight	Dry Weight	Area of X-Section	Ultimate load	Ultimate	Water Absorpti	Remarks
	Mark	DD	ММ	YYYY	(in)	_	(Kg/ gms)		(Imp.Tons)		on (%)	Kemarks
1	5000 Psi	23	9	2021	6Diax12		14	28.28	63	4990		Engraved
2	5000 Psi	23	9	2021	6Diax12		14	28.28	51	4040		Engraved
3												
4												
5					-	Blindin	GAIL.					
6					-6	READ IN THE NAME OF THE						
7					N I	CREATED SIGN	30 - E					
8					THE STATE OF THE S	-						
9					- 40							
10						LAHUY	<u></u>					
11												
12												
13												
14												
15												
16												

Witnessed by:

Results can also be seen on website https://civil.uet.edu.pk/concrete-laboratory-reports1/

- 1. * as engraved on the specimens (if any)
- 2. ** BS3921 requires average of ten clay brick samples for crushing strength and water absorption
- 3. *** BS5328 requires mean of two cube sample strength at 28 days as characteristic strength
- 4. **** ACl318-08 requires mean of two sample (6"diax12" cylinder) strength at 28 days as comprerssive strength

- 1.The laboratory is not responsible for sampling, originality and construction conditions (such as mix proportion, w/c ratio, compaction, curing and quality of ingredients)
- 2. The test results are recommended to be interpreted in the light of above factors by the engineer.



University of Engineering and Technology, Lahore. Pakistan
Landline: 042-99029245 & 042-99029202 Mobile: 0307-0496895

ORIGINAL
A carbon copy for the report has been retained in the lab for record.

1999 Dr. M. Yousaf

To: Muhammad Azeem (Operation Manager)

Amer Adnan Associates, 17-E-II, Gulberg III, Lahore.

Project: Hotel Building at 24-A Block E/2 at Gulberg III, Lahore.

 Our Ref. No. CL/CED/ 6010
 Dated:
 07-10-21
 Test Specification

 Your Ref. No.
 AAA/ 24A/ 0050
 Dated:
 29-09-21
 (ASTM C39)

COMPRESSION TEST REPORT

Concrete Cubes/Concrete Cylinders/Bricks/Cores/Tuff Tiles/Pavers

Specimens received on: 29-09-21 Tested on: 01-10-21 in dry/wet condition





Sr. No.	Mark*	Casting Date*			Size	Wet Weight	Dry Weight	Area of X-Section	Ultimate load	Ultimate Stress	Water Absorpti	Remarks
	man	DD	ММ	YYYY	(in)	_	(Kg/ gms)		(Imp.Tons)		on (%)	Kemarks
1	3000 Psi	31	8	2021	6Diax12		14	28.28	44	3485		Non Engraved
2	3000 Psi	31	8	2021	6Diax12		14.2	28.28	38	3010		Non Engraved
3												
4						-						
5					4 (4)	31111111	BARRA					
6					-6	READ IN THE NAME OF THE	7					
7					SIT	الله CREATE						
8					T. C.		0,0					
9					- 40		= ==					
10						LAHUY						
11												
12												
13					-							
14												
15												
16												

Witnessed by:

Results can also be seen on website https://civil.uet.edu.pk/concrete-laboratory-reports1/

- 1. * as engraved on the specimens (if any)
- 2. ** BS3921 requires average of ten clay brick samples for crushing strength and water absorption
- 3. *** BS5328 requires mean of two cube sample strength at 28 days as characteristic strength
- 4. **** ACl318-08 requires mean of two sample (6"diax12" cylinder) strength at 28 days as comprerssive strength

- 1.The laboratory is not responsible for sampling, originality and construction conditions (such as mix proportion, w/c ratio, compaction, curing and quality of ingredients)
- 2. The test results are recommended to be interpreted in the light of above factors by the engineer.



University of Engineering and Technology, Lahore. Pakistan Landline: 042-99029245 & 042-99029202 Mobile: 0307-0496895

ORIGINAL
A carbon copy for the report has been retained in the lab for record.

2002 Engr Ubaid

To: Mr. Muhammad Khalid Zaman (Resident Engineer)

Engineering Consultany Services punjab (Pvt.) Ltd. Gulberg III, Lahore.

Project: Constrution, installation And O& M Of Surface Water Treatment Plant at Rural Area, Sahiwal

Our Ref. No. CL/CED/ 6011 Dated: 07-10-21

Your Ref. No. ECSP/Papa/CZ-RN-11 Dated: 29-09-21

COMPRESSION TEST REPORT

Concrete Cubes/Concrete Cylinders/Bricks/Cores/Tuff Tiles/Pavers

Specimens received on: 30-09-21 Tested on: 06-10-21 in dry/wet condition



Test Specification

(ASTM C39)



Sr. No.	Mark*	Casting Date*			Size	Wet Weight	Dry Weight	Area of X-Section	Ultimate load	Ultimate Stress	Water Absorpti	Remarks
		DD	мм	YYYY	(in)	(Kg/ gms)	(Kg/ gms)		(Imp.Tons)		on (%)	
	Chak 25/1AL (3000 Psi)	27	8	2021	6Diax12		13.6	28.28	60	4752		Non Engraved
2	Psi) Chak 25/1AL (3000 Psi)	27	8	2021	6Diax12		13.6	28.28	69	5465		Non Engraved
3												
4												
5					4 (1)	Blinant	BAR.					
6						READ IN THE NAME OF THE						
7					- Es	CREATER SIL	<u>الاق</u>					
8					E	-						
9					- 40		100					
10						LAHUY						
11												
12												
13												
14												
15												
16												

Witnessed by:

Results can also be seen on website https://civil.uet.edu.pk/concrete-laboratory-reports1/

- 1. * as engraved on the specimens (if any)
- 2. ** BS3921 requires average of ten clay brick samples for crushing strength and water absorption
- 3. *** BS5328 requires mean of two cube sample strength at 28 days as characteristic strength
- 4. **** ACl318-08 requires mean of two sample (6"diax12" cylinder) strength at 28 days as comprerssive strength

- 1.The laboratory is not responsible for sampling, originality and construction conditions (such as mix proportion, w/c ratio, compaction, curing and quality of ingredients)
- 2. The test results are recommended to be interpreted in the light of above factors by the engineer.



University of Engineering and Technology, Lahore. Pakistan
Landline: 042-99029245 & 042-99029202 Mobile: 0307-0496895

ORIGINAL
A carbon copy for the report has been retained in the lab for record.

1945 Dr. M. Yousaf

To: Mr.M.Shahbaz

M/s Imperium Hospitality, Lahore.

Project: Nil

 Our Ref. No. CL/CED/
 5057
 Dated:
 30-09-21
 Test Specification

 Your Ref. No.
 IHPL-Con-406
 Dated:
 13-09-21
 (ASTM C39)

COMPRESSION TEST REPORT

Concrete Cubes/Concrete Cylinders/Bricks/Cores/Tuff Tiles/Pavers

Specimens received on: 21-09-21 Tested on: 28-09-21 in dry/wet condition





Sr. No.	Mark*	Casting Date*			Size	Wet Weight	Dry Weight	Area of X-Section	Ultimate load	Ultimate Stress	Absorpti	Remarks
		DD	MM	YYYY	(in)	(Kg/ gms)	(Kg/ gms)	(Sq. in)	(Imp.Tons)	(psi)	on (%)	
1	12(4000) Psi	24	8	2021	6Diax12		14.2	28.28	84	6653		Non Engraved
2	10(4000) Psi	24	8	2021	6Diax12		14	28.28	69	5465		Non Engraved
3	11(8000) Psi	24	8	2021	6Diax12		14.2	28.28	70	5545		Non Engraved
4												
5					4 (1	Blissin	BAND					
6					-87	READ IN THE NAME	7					
7					- Es	CREATER-	<u>الاق</u>					
8					E	-						
9					%		120					
10						LAHUN						
11												
12												
13												
14												
15												
16												

Witnessed by: Rafi Ullah 34501-0261679-5 Usama Tariq 35401-6915176-9

Results can also be seen on website https://civil.uet.edu.pk/concrete-laboratory-reports1/

- 1. * as engraved on the specimens (if any)
- 2. ** BS3921 requires average of ten clay brick samples for crushing strength and water absorption
- 3. *** BS5328 requires mean of two cube sample strength at 28 days as characteristic strength
- 4. **** ACl318-08 requires mean of two sample (6"diax12" cylinder) strength at 28 days as comprerssive strength

- 1. The laboratory is not responsible for sampling, originality and construction conditions (such as mix proportion, w/c ratio, compaction, curing and quality of ingredients)
- 2. The test results are recommended to be interpreted in the light of above factors by the engineer.