

Plain and Reinforced Concrete Laboratory Civil Engineering Department

University of Engineering and Technology, Lahore. Pakistan Landline: 042-99029245 & 042-99029202 Mobile: 0307-0496895

ORIGINAL
A carbon copy for
the report has
been retained in
the lab for record.

tł

4379 Dr. Umbreen

To: Mr. Aamir Shahzad Alvi

Project Manager, High-Q Constructions.

Project: Construction of HIGH-Q Mall & Offices at 3-A, Gulberg II, Lahore.

Our Ref. No. CL/	CED/ 599	Dated:	13-12-22	Test Specification
Your Ref. No.	QC/HQ/CIVIL/44	Dated:	05-12-22	(ASTM C39)

COMPRESSION TEST REPORT



Concrete Cubes/Concrete Cylinders/Bricks/Cores/Tuff Tiles/Pavers

Specimens received on:		0	08-12-22 Tested on:		12-1	12-12-22 in dry/wet		t condition			itske g	
Sr. No.	Mark*		•	Date* YYYY	Size (in)	Wet Weight	Dry Weight (Kg/ gms)	Area of X-Section (Sq. in)	Ultimate load (Imp.Tons)	Ultimate Stress (psi)	Water Absorpti on (%)	Remarks
1	Column (8000 Psi)	7	11	2022	(III) 6Diax12	(r.g/ gills) 	(r.g/ gills) 13.4	28.28	(imp. rons) 108	(psi) 8554		Non Engraved
	. ,	-		-								
2	Column (8000 Psi)	7	11	2022	6Diax12		14	28.28	122	9663		Non Engraved
3	Column (8000 Psi)	7	11	2022	6Diax12		13.8	28.28	116	9188		Non Engraved
4	Column (8000 Psi)	8	11	2022	6Diax12		14	28.28	122	9663		Non Engraved
5	Column (8000 Psi)	8	11	2022	6Diax12	GINE	13.8	28.28	118	9347		Non Engraved
6	Column (8000 Psi)	8	11	2022	6Diax12	READIN	13.8	28.28	124	9822		Non Engraved
7	Retaining Wall (6000 Psi)	9	11	2022	6Diax12	DHE NAME OF THY LORD WHO	13.8	28.28	116	9188		Non Engraved
8	Retaining Wall (6000 Psi)	9	11	2022	6Diax12		14	28.28	114	9030		Non Engraved
9	Retaining Wall (6000 Psi)	9	11	2022	6Diax12		13.4	28.28	96	7604		Non Engraved
10	Column (8000 Psi)	9	11	2022	6Diax12	-LA	13.6	28.28	122	9663		Non Engraved
11	Column (8000 Psi)	9	11	2022	6Diax12		14	28.28	114	9030		Non Engraved
12	Column (8000 Psi)	9	11	2022	6Diax12		13.8	28.28	128	10139		Non Engraved
13												
14												
15												
16												
Witness	sed by:											

Results can also be seen on website https://civil.uet.edu.pk/concrete-laboratory-reports1/

1. * as engraved on the specimens (if any)

2. ** BS3921 requires average of ten clay brick samples for crushing strength and water absorption

3. *** BS5328 requires mean of two cube sample strength at 28 days as characteristic strength

4. **** ACI318-08 requires mean of two sample (6"diax12" cylinder) strength at 28 days as compressive strength

 $\underline{\textbf{Note:}}$ Above results pertain to the unsealed samples supplied to the laboratory

1. The laboratory is not responsible for sampling, originality and construction conditions (such as mix proportion, w/c ratio, compaction, curing and quality of ingredients) 2. The test results are recommended to be interpreted in the light of above factors by the engineer.



Our Ref. No. CL/CED/ 600	Dated:	13-12-22	Test Specification
Your Ref. No. IMP/PM/66/09/06	Dated:	08-12-22	(ASTM C39)

COMPRESSION TEST REPORT



Concrete Cubes/Concrete Cylinders/Bricks/Cores/Tuff Tiles/Pavers

Specim	ens received on:	0	8-12	-22	Tested on:	13-1	2-22	in dry/wet condition			Ö	jester
Sr. No.	Mark*		•	Date* YYYY	Size (in)	Wet Weight (Kg/ gms)	Dry Weight (Kg/ gms)	Area of X-Section (Sq. in)		Ultimate Stress (psi)	Water Absorpti on (%)	Remarks
1	Lift Wall (6000 Psi)	9	11	2022	6Diax12		13.2	28.28	94	7446		Non Engraved
2	Lift Wall (6000 Psi)	9	11	2022	6Diax12		13.4	28.28	98	7762		Non Engraved
3												
4							-					
5						HINE	RIATE					
6)	READ IN	NOT THE					
7						DHE NAME OF THY CORD VIND	-4	FP				
8												
9						· · · ·	1					
10					- <	-LA	INRE .					
11												
12												
13												
14												
15												
16												
Witness	sed by: Mr. Husnai	n Im	ran.	CNIC #	# 35202-66343	87-3						

Witnessed by: Mr. Husnain Imran, CNIC # 35202-6634387-3

Results can also be seen on website https://civil.uet.edu.pk/concrete-laboratory-reports1/

1. * as engraved on the specimens (if any)

2. ** BS3921 requires average of ten clay brick samples for crushing strength and water absorption

3. *** BS5328 requires mean of two cube sample strength at 28 days as characteristic strength

4. **** ACI318-08 requires mean of two sample (6"diax12" cylinder) strength at 28 days as comprensive strength

 $\underline{\textbf{Note:}}$ Above results pertain to the unsealed samples supplied to the laboratory

1. The laboratory is not responsible for sampling, originality and construction conditions (such as mix proportion, w/c ratio, compaction, curing and quality of ingredients) 2. The test results are recommended to be interpreted in the light of above factors by the engineer.



Our Ref. No. CL/CED	0/ 601	Dated:	13-12-22	Test Specification
Your Ref. No. IN	IP/PM/66/09/06	Dated:	08-12-22	(ASTM C39)

COMPRESSION TEST REPORT

Concrete Cubes/Concrete Cylinders/Bricks/Cores/Tuff Tiles/Pavers

Specim	ens received on:	0	8-12	-22	Tested on:	13-1	2-22	in dry/wet condition				its de la
Sr. No.	Mark*		•	Date* YYYY	Size (in)	Wet Weight (Kg/ gms)	Dry Weight (Kg/ gms)	Area of X-Section (Sq. in)	Ultimate load (Imp.Tons)		Water Absorpti on (%)	Remarks
1	Slab (4500 Psi)	7	11	2022	6Diax12		13.2	28.28	69	5465		Non Engraved
2	Slab (4500 Psi)	7	11	2022	6Diax12		13.2	28.28	65	5149		Non Engraved
3												
4												
5						RINE	RIATE					
6						I READ IN						
7					11	DHE NHOLE <u>OE</u> THY LORD VIND	144	FC				
8					188							
9						-	1					
10						(A	INRE .					
11												
12												
13												
14												
15												
16												
Witness	ed by: Mr. Husnai	in Im	ran,	CNIC #	# 35202-663438	87-3						

Results can also be seen on website <u>https://civil.uet.edu.pk/concrete-laboratory-reports1/</u>

1. * as engraved on the specimens (if any)

2. ** BS3921 requires average of ten clay brick samples for crushing strength and water absorption

3. *** BS5328 requires mean of two cube sample strength at 28 days as characteristic strength

4. **** ACI318-08 requires mean of two sample (6"diax12" cylinder) strength at 28 days as comprerssive strength

 $\underline{\textbf{Note:}}$ Above results pertain to the unsealed samples supplied to the laboratory

1. The laboratory is not responsible for sampling, originality and construction conditions (such as mix proportion, w/c ratio, compaction, curing and quality of ingredients) 2. The test results are recommended to be interpreted in the light of above factors by the engineer.





ORIGINAL A carbon copy for the report has been retained in the lab for record.

> 4361 Dr. Aqsa

To: Mr. Amein Uddin, PM Project Majeed Associates Pvt. Ltd. Karachi.

Project: Construction of ABL Bank Expo Centre Johar Town, Lahore. (Tetra Ready Mix).

Our Ref. No. CL/CED/ 602	Dated:	13-12-22	Test Specification
Your Ref. No. Nil	Dated:	06-12-22	(ASTM C39)

COMPRESSION TEST REPORT

Concrete Cubes/Concrete Cylinders/Bricks/Cores/Tuff Tiles/Pavers

Specim	ens received on:	0	6-12	-22	Tested on:	13-1	12-22	in dry/wet condition		Ë	je state si	
Sr. No.	Mark*		•	Date* YYYY	Size (in)	Wet Weight (Ka/ ams)	Dry Weight (Kg/ gms)	Area of X-Section (Sq. in)		Ultimate Stress (psi)	Water Absorpti on (%)	Remarks
1	1:1.5:3 (4000 Psi)	29	11	2022	6Diax12		13.2	28.28	73	5782		Non Engraved
2	1:1.5:3 (4000 Psi)	29	11	2022	6Diax12		13	28.28	71	5624		Non Engraved
3												
4												
5					/	ARTINE	RING					
6					-)	NEAD W	ALS D					
7					12	DHE NAULE OF THY LORD WHO						
8					- 38							
9						·						
10					<	LA	IORE .					
11												
12												
13												
14												
15												
16												
Witness	sed by:											

vitnessea by:

Results can also be seen on website https://civil.uet.edu.pk/concrete-laboratory-reports1/

1. * as engraved on the specimens (if any)

2. ** BS3921 requires average of ten clay brick samples for crushing strength and water absorption

3. *** BS5328 requires mean of two cube sample strength at 28 days as characteristic strength

4. **** ACI318-08 requires mean of two sample (6"diax12" cylinder) strength at 28 days as comprensive strength

 $\underline{\textbf{Note:}}$ Above results pertain to the unsealed samples supplied to the laboratory

1. The laboratory is not responsible for sampling, originality and construction conditions (such as mix proportion, w/c ratio, compaction, curing and quality of ingredients) 2. The test results are recommended to be interpreted in the light of above factors by the engineer.





4360

Dr. Aqsa

To: Mr. Sufyan Mehmood

Creative Home, Shop # 2, Izmir Housing Society, Lahore.

Project: Construction of 12-A Commercial Izmir Town, Lahore

Our Ref. No. CL/CED/ 603	Dated:	13-12-22	Test Specification
Your Ref. No. Nil	Dated:	06-12-22	(ASTM C39)

COMPRESSION TEST REPORT

Concrete Cubes/Concrete Cylinders/Bricks/Cores/Tuff Tiles/Pavers

Specim	ens received on:	0	6-12	-22	Tested on:	13-1	2-22	in dry/wet condition			Ċ	jesteg
Sr. No.	Mark*	Cas DD	•	Date* YYYY	Size (in)	Wet Weight (Kg/ gms)	Dry Weight (Kg/ gms)	Area of X-Section (Sq. in)		Ultimate Stress (psi)	Water Absorpti on (%)	Remarks
1	(3000 Psi)	16	10	2022	6Diax12		12.8	28.28	59	4673		Non Engraved
2	(3000 Psi)	16	10	2022	6Diax12		13.2	28.28	57	4515		Non Engraved
3												
4												
5					/	HINE	RINA					
6)	READ IN	PAUS D					
7					41	DHE NAME OF THY CORD WHO		EP-				
8					88							
9						2		7				
10					- <	-LA	IORE .					
11												
12												
13												
14												
15												
16												
Witness	ed by:											

vitnessea by:

Results can also be seen on website https://civil.uet.edu.pk/concrete-laboratory-reports1/

1. * as engraved on the specimens (if any)

2. ** BS3921 requires average of ten clay brick samples for crushing strength and water absorption

3. *** BS5328 requires mean of two cube sample strength at 28 days as characteristic strength

4. **** ACI318-08 requires mean of two sample (6"diax12" cylinder) strength at 28 days as comprensive strength

 $\underline{\textbf{Note:}}$ Above results pertain to the unsealed samples supplied to the laboratory

1. The laboratory is not responsible for sampling, originality and construction conditions (such as mix proportion, w/c ratio, compaction, curing and quality of ingredients) 2. The test results are recommended to be interpreted in the light of above factors by the engineer.

