

Dated:

10-10-23

(ASTM C39)

Your Ref. No. HMBDPL/S.O/10/23/73th (LHR)

COMPRESSION TEST REPORT

Concrete Cubes/Concrete Cylinders/Bricks/Cores/Tuff Tiles/Pavers

Specim	1	10-10-23		Tested on:	10-10-23		in dry/wet condition				je sledo	
Sr. No.	Mark*	Cas DD	ting MM	Date* YYYY	Size (in)	Wet Weight (Kg/ gms)	Dry Weight (Kg/ gms)	Area of X-Section (Sq. in)	Ultimate load (Imp.Tons)	Ultimate Stress (psi)	Water Absorpti on (%)	Remarks
1	CT-37 (6000 Psi)	11	9	2023	6Diax12		13.2	28.28	81	6416		Non Engraved
2	CT-37 (6000 Psi)	11	9	2023	6Diax12		13.4	28.28	81	6416		Non Engraved
3	CT-37 (6000 Psi)	11	9	2023	6Diax12		14	28.28	81	6416		Non Engraved
4												
5												
6												
7												
8												
9												
10												
11												
12												
13												
14												
15												
16												
Witness	ed by: Mr. M. Azha	ır Sa	eed,	CNIC 3	32301-4082540	-3; Mr. Rah	eel Ihtishai	m, CNIC 3	5201-660432	28-3		

Results can also be seen on website https://civil.uet.edu.pk/concrete-laboratory-reports1/

1. * as engraved on the specimens (if any)

2. ** BS3921 requires average of ten clay brick samples for crushing strength and water absorption

3. *** BS5328 requires mean of two cube sample strength at 28 days as characteristic strength

4. **** ACI318-08 requires mean of two sample (6"diax12" cylinder) strength at 28 days as comprensive strength

Note: Above results pertain to the unsealed samples supplied to the laboratory

1. The laboratory is not responsible for sampling, originality and construction conditions (such as mix proportion, w/c ratio, compaction, curing and quality of ingredients)

2. The test results are recommended to be interpreted in the light of above factors by the engineer.



Our Ref. No. CL/C	ED/ 3117	Dated:	10-10-23	Test Specification
Your Ref. No.	AIz/CT/UET/008	Dated:	09-10-23	(ASTM C39)

COMPRESSION TEST REPORT

Concrete Cubes/Concrete Cylinders/Bricks/Cores/Tuff Tiles/Pavers

Specim	09-10-23		-23	Tested on:	10-10-23		in dry/wet condition				jeskego	
Sr. No.	Mark*	Cas DD	ting MM	Date* YYYY	Size (in)	Wet Weight (Kg/ gms)	Dry Weight (Kg/ gms)	Area of X-Section (Sq. in)	Ultimate Ioad (Imp.Tons)	Ultimate Stress (psi)	Water Absorpti on (%)	Remarks
1	3000 Psi	20	9	2023	6Diax12		14	28.28	47	3723		Non Engraved
2	3000 Psi	20	9	2023	6Diax12		13.2	28.28	17	1347	-	Non Engraved
3	3000 Psi	20	9	2023	6Diax12		13.4	28.28	41	3248		Non Engraved
4												
5												
6												
7												
8												
9												
10												
11												
12												
13												
14												
15												
16												

Witnessed by: Nil

Results can also be seen on website https://civil.uet.edu.pk/concrete-laboratory-reports1/

1. * as engraved on the specimens (if any)

2. ** BS3921 requires average of ten clay brick samples for crushing strength and water absorption

3. *** BS5328 requires mean of two cube sample strength at 28 days as characteristic strength

4. **** ACI318-08 requires mean of two sample (6"diax12" cylinder) strength at 28 days as comprensive strength

Note: Above results pertain to the unsealed samples supplied to the laboratory

1. The laboratory is not responsible for sampling, originality and construction conditions (such as mix proportion, w/c ratio, compaction, curing and quality of ingredients)

2. The test results are recommended to be interpreted in the light of above factors by the engineer.



To:

Director Operations, Pakmix Readymix Concrete

Project: Al Azamiyya Phase-I Our Ref. No. CL/CED/ 3118 Your Ref. No. Nil

Dated: Dated: 10-10-23 09-10-23 Test Specification

6037

(ASTM C39)



COMPRESSION TEST REPORT

Concrete Cubes/Concrete Cylinders/Bricks/Cores/Tuff Tiles/Pavers

Specim	ens received on:	0	9-10	-23	Tested on:	10-1	10-23	in dry/we	t condition		0	i Cradit di
Sr. No.	Mark*	Cas	Casting Date*		Size	Wet Weight	Dry Weight (Ka/ ams)	Area of X-Section	Ultimate load (Imp Tons)	Ultimate Stress (psi)	Water Absorpti on (%)	Remarks
1	Slab (3000 Psi),	20	9	2023	6Diax12	(itg/ giiis) 	14	28.28	51	4040		Non Engraved
2	(Plant) Slab (3000 Psi),	20	9	2023	6Diax12		14	28.28	49	3881		Non Engraved
3	Slab (3000 Psi), (Plant)	20	9	2023	6Diax12		13.6	28.28	43	3406		Non Engraved
4												
5												
6												
7												
8												
9												
10												
11												
12												
13												
14												
15												
16												

Witnessed by: Nil

Results can also be seen on website https://civil.uet.edu.pk/concrete-laboratory-reports1/

1. * as engraved on the specimens (if any)

2. ** BS3921 requires average of ten clay brick samples for crushing strength and water absorption

3. *** BS5328 requires mean of two cube sample strength at 28 days as characteristic strength

4. **** ACI318-08 requires mean of two sample (6"diax12" cylinder) strength at 28 days as comprensive strength

Note: Above results pertain to the unsealed samples supplied to the laboratory

1.The laboratory is not responsible for sampling, originality and construction conditions (such as mix proportion, w/c ratio, compaction, curing and quality of ingredients)

2. The test results are recommended to be interpreted in the light of above factors by the engineer.



Civil Engineering Department

University of Engineering and Technology, Lahore. Pakistan Landline: 042-99029245 & 042-99029202 Mobile: 0307-0496895



ORIGINAL A carbon copy for the report has been retained in the lab for record.

> 6044 Dr. Aqsa

To: Engr's Abdul Waheed

Project Engineer, OZ Developers Pvt. Ltd.

Project: Constructing a High Rise Building "Bahria Sky" at Bahria Orchard Phase-4 Lahore.

Our Ref. No. CL/CEE	D/ 3119	Dated:	10-10-23	Test Specification
Your Ref. No.	lil	Dated:	10-10-23	(ASTM C39)

COMPRESSION TEST REPORT

Concrete Cubes/Concrete Cylinders/Bricks/Cores/Tuff Tiles/Pavers



Results can also be seen on website https://civil.uet.edu.pk/concrete-laboratory-reports1/

1. * as engraved on the specimens (if any)

2. ** BS3921 requires average of ten clay brick samples for crushing strength and water absorption

3. *** BS5328 requires mean of two cube sample strength at 28 days as characteristic strength

4. **** ACI318-08 requires mean of two sample (6"diax12" cylinder) strength at 28 days as comprensive strength

Note: Above results pertain to the unsealed samples supplied to the laboratory

1. The laboratory is not responsible for sampling, originality and construction conditions (such as mix proportion, w/c ratio, compaction, curing and quality of ingredients)

2. The test results are recommended to be interpreted in the light of above factors by the engineer.



Civil Engineering Department

University of Engineering and Technology, Lahore. Pakistan Landline: 042-99029245 & 042-99029202 Mobile: 0307-0496895



ORIGINAL A carbon copy for the report has been retained in the lab for record.

5955 Dr. Asad Gillani

To: Mr. M. Aslam

Projects Engineer, HKB Retail (SMC-Pvt) Ltd.

Project: Construction of Mixed Use Building at Noor Jahan Road, Liberty Market, Lahore.

Our Ref. No. CL/	CED/ 3120	Dated:	10-10-23	Test Specification
Your Ref. No.	BAB/CR/030	Dated:	21-09-23	(ASTM C39)

COMPRESSION TEST REPORT

Concrete Cubes/Concrete Cylinders/Bricks/Cores/Tuff Tiles/Pavers



Specime	22-09-23			Tested on:	09-10-23		in dry/wet condition				je ka	
Sr. No.	Mark*	Cas	Casting Date*		Size	Wet Weight	Dry Weight	Area of X-Section	Ultimate load	Ultimate Stress	Water Absorpti on (%)	Remarks
1	Columns	12	8	2023	6Diax12	(rtg/ gills) 	(rtg/ gills) 13.2	28.28	(imp.rons) 72	(psi) 5703		Engraved
2	Columns (4000 Psi)	12	8	2023	6Diax12		13.2	28.28	68	5386		Engraved
3	Columns (4000 Psi)	17	8	2023	6Diax12		13.4	28.28	60	4752		Engraved
4	Columns (4000 Psi)	17	8	2023	6Diax12		13.4	28.28	58	4594		Engraved
5	Columns (4000 Psi)	19	8	2023	6Diax12		13.4	28.28	60	4752		Engraved
6	Columns (4000 Psi)	19	8	2023	6Diax12		13.6	28.28	54	4277		Engraved
7	Columns (4000 Psi)	25	8	2023	6Diax12		13.6	28.28	62	4911		Engraved
8	Columns (4000 Psi)	25	8	2023	6Diax12		13.8	28.28	60	4752		Engraved
9	Columns (4000 Psi)	13	9	2023	6Diax12		13.7	28.28	58	4594		Engraved
10	Columns (4000 Psi)	13	9	2023	6Diax12		13.6	28.28	60	4752		Engraved
11												
12												
13										-		
14										-		
15												
16												
Witness	Witnessed by: Engr. M. Jamil Ahmed											

Results can also be seen on website https://civil.uet.edu.pk/concrete-laboratory-reports1/

1. * as engraved on the specimens (if any)

2. ** BS3921 requires average of ten clay brick samples for crushing strength and water absorption

3. *** BS5328 requires mean of two cube sample strength at 28 days as characteristic strength

4. **** ACI318-08 requires mean of two sample (6"diax12" cylinder) strength at 28 days as comprensive strength

Note: Above results pertain to the unsealed samples supplied to the laboratory

1. The laboratory is not responsible for sampling, originality and construction conditions (such as mix proportion, w/c ratio, compaction, curing and quality of ingredients) 2. The test results are recommended to be interpreted in the light of above factors by the engineer.

Supervisor (Lab)



Civil Engineering Department

University of Engineering and Technology, Lahore. Pakistan Landline: 042-99029245 & 042-99029202 Mobile: 0307-0496895



ORIGINAL A carbon copy for the report has been retained in the lab for record.

> 6026 Dr. Aqsa

To: Engr. Abdul Waheed

Project Engineer, OZ Developers Pvt. Ltd.

Project: Constructing a High Rise Building "Bahria Sky" at Bahria Orchard Phase-4 Lahore.

Our Ref. No. CL/CE	D/ 3121	Dated:	10-10-23	Test Specification
Your Ref. No.	Nil	Dated:	06-10-23	(ASTM C39)

COMPRESSION TEST REPORT

Concrete Cubes/Concrete Cylinders/Bricks/Cores/Tuff Tiles/Pavers



Results can also be seen on website https://civil.uet.edu.pk/concrete-laboratory-reports1/

1. * as engraved on the specimens (if any)

2. ** BS3921 requires average of ten clay brick samples for crushing strength and water absorption

3. *** BS5328 requires mean of two cube sample strength at 28 days as characteristic strength

4. **** ACI318-08 requires mean of two sample (6"diax12" cylinder) strength at 28 days as comprensive strength

Note: Above results pertain to the unsealed samples supplied to the laboratory

1. The laboratory is not responsible for sampling, originality and construction conditions (such as mix proportion, w/c ratio, compaction, curing and quality of ingredients)

2. The test results are recommended to be interpreted in the light of above factors by the engineer.



Civil Engineering Department

University of Engineering and Technology, Lahore. Pakistan Landline: 042-99029245 & 042-99029202 Mobile: 0307-0496895



Dated:

Dated:

10-10-23

09-10-23

To: Mr. Ghulam Fareed

Material Engineer, Strong Ready Mix (Company: Bilal Contractors)

Project: Construction of Alhassan Islamic Center

Our Ref. No. CL/CED/ 3122

Your Ref. No. Nil

COMPRESSION TEST REPORT

Concrete Cubes/Concrete Cylinders/Bricks/Cores/Tuff Tiles/Pavers

Specim	ens received on:	0	9-10	-23	Tested on:	10-1	0-23	in dry/wet	t condition		[16236295
Sr. No.	Mark*	Cas	Casting Date*		Size (in)	Wet Weight (Ka/ ams)	Dry Weight (Ka/ ams)	Area of X-Section (Sg. in)	Ultimate load (Imp.Tons)	Ultimate Stress (psi)	Water Absorpti on (%)	Remarks
1	Raft (3000 Psi)	30	9	2023	6Diax12		13.8	28.28	50	3960		Non Engraved
2	Raft (3000 Psi)	30	9	2023	6Diax12		14	28.28	61	4832		Non Engraved
3	Raft (3000 Psi)	30	9	2023	6Diax12		14	28.28	65	5149		Non Engraved
4	Raft (3000 Psi)	30	9	2023	6Diax12		14.2	28.28	54	4277		Non Engraved
5	Raft (3000 Psi)	30	9	2023	6Diax12		14.4	28.28	58	4594		Non Engraved
6	Raft (3000 Psi)	30	9	2023	6Diax12		14.4	28.28	68	5386		Non Engraved
7												
8												
9												
10												
11												
12												
13												
14												
15												
16												
1.4.0.4												

Witnessed by:

Results can also be seen on website https://civil.uet.edu.pk/concrete-laboratory-reports1/

1. * as engraved on the specimens (if any)

2. ** BS3921 requires average of ten clay brick samples for crushing strength and water absorption

3. *** BS5328 requires mean of two cube sample strength at 28 days as characteristic strength

4. **** ACI318-08 requires mean of two sample (6"diax12" cylinder) strength at 28 days as comprensive strength

Note: Above results pertain to the unsealed samples supplied to the laboratory

1. The laboratory is not responsible for sampling, originality and construction conditions (such as mix proportion, w/c ratio, compaction, curing and quality of ingredients)

2. The test results are recommended to be interpreted in the light of above factors by the engineer.



6035 Dr. Aqsa

Test Specification

(ASTM C39)



Plain and Reinforced Concrete Laboratory Civil Engineering Department

University of Engineering and Technology, Lahore. Pakistan

Landline: 042-99029245 & 042-99029202

Mobile: 0307-0496895

ORIGINAL A carbon copy for the report has been retained in the lab for record.

> 5938 Dr. Aqsa

To: Mr. Kashif ul Haq

Resident Engineer, G3 Engg. Consultants (Pvt) Ltd. University of Narowal, New Campus Narowal.

Project: Strengthening & Expansion of University of Gujrat & Allied Campuses (Narowal Component)

Our Ref. No. CL/C	ED/ 3123	Dated:	10-10-23	Test Specification
Your Ref. No.	G3/UoN-RE/384	Dated:	08-09-23	(BS 3921**)

COMPRESSION TEST REPORT



Concrete Cubes/Concrete Cylinders/Bricks/Cores/Tuff Tiles/Pavers -----

Specimens received on:		20-09-23		-23	Tested on:	10-10-23		in dry/wet condition				
Sr. No.	Mark*	Cas	ting	Date*	Size (in)	Wet Weight (Ka/ ams)	Dry Weight (Ka/ ams)	Area of X-Section (Sg. in)	Ultimate load (Imp.Tons)	Ultimate Stress (psi)	Water Absorpti on (%)	Remarks
1	PL				8.6 x 4.2 x 2.7	3295	2715	36.12	39	2419	21.36	Machine Made
2	PL				8.5 x 4.3 x 2.9	3330	2755	36.55	38	2329	20.87	Machine Made
3	PL				8.5 x 4.2 x 2.9	3290	2735	35.7	48	3012	20.29	Machine Made
4	PL				8.4 x 4.2 x 2.8	3210	2670	35.28	41	2603	20.22	Machine Made
5	PL				8.5 x 4.2 x 2.8	3280	2740	35.7	43	2698	19.71	Machine Made
6	м				8.6 x 4.2 x 2.6	3015	2505	36.12	29	1798	20.36	Machine Made
7	м				8.5 x 4.2 x 2.7	3115 WHO	2630	35.7	35	2196	18.44	Machine Made
8	м				8.4 x 4. <mark>2 x 2.8</mark>	3140	2655	35.28	28	1778	18.27	Machine Made
9	м				8.5 x 4.2 x 2.9	3110	2580	35.7	22	1380	20.54	Machine Made
10					<	/ A	IOR <u>E</u>					
11												
12												
13												
14												
15												
16												
Witness	ed by:											

witnessea by:

Results can also be seen on website https://civil.uet.edu.pk/concrete-laboratory-reports1/

1. * as engraved on the specimens (if any)

2. ** BS3921 requires average of ten clay brick samples for crushing strength and water absorption

3. *** BS5328 requires mean of two cube sample strength at 28 days as characteristic strength

4. **** ACI318-08 requires mean of two sample (6"diax12" cylinder) strength at 28 days as comprensive strength

Note: Above results pertain to the unsealed samples supplied to the laboratory

1. The laboratory is not responsible for sampling, originality and construction conditions (such as mix proportion, w/c ratio, compaction, curing and quality of ingredients) 2. The test results are recommended to be interpreted in the light of above factors by the engineer.



Civil Engineering Department

University of Engineering and Technology, Lahore. Pakistan Landline: 042-99029245 & 042-99029202 Mobile: 0307-0496895

6039 Dr. Aqsa

Test Specification

(----)

To: Mr. Qaiser Maqbool Ittefaq Building Solutions Pvt. Ltd.

Project: New Apparel Facility, Ferozwattwan

Our Ref. No. CL/CED/ 3124

Your Ref. No. IBS/SD/ST12

COMPRESSION TEST REPORT



Specimo	ens received on:	0	9-10	-23	Tested on:	10-1	0-23	in dry/we	t condition			ONLINE REPORT
Sr. No.	Mark*	Cas	Casting Date*		Size	Wet Weight	Dry Weight	Area of X-Section	Ultimate Ioad	Ultimate Stress	Water Absorpti	Remarks
		DD	MM	YYYY	(in)	(Kg/ gms)	(Kg/ gms)	(Sq. in)	(Imp.Tons)	(psi)	оп (%)	
1	I-Section, Grey, 60mm				2.4" thick		3840	41.83	100	5355		
2	I-Section, Grey, 60mm				2.4" thick		3640	41.83	110	5891		
3	I-Section, Grey, 60mm				2.4" thick		3675	41.83	113	6051		
4	I-Section, Grey, 60mm				2.4" thick		3590	41.83	85	4552		
5	I-Section, Grey, 60mm				2.4" thick	NETNE	3710	41.83	99	5301		
6	I-Section, Grey, 60mm				2.4" thick	READ IN	3670	41.83	123	6587		
7	I-Section, Grey, 60mm				2.4" thick	OF THY CREATES	3745	41.82	116	6213		
8					1			5-				
9					- /	20-		?				
10					<		IOR -					
11												
12												
13												
14												
15												
16												

Dated:

Dated:

10-10-23

09-10-23

Witnessed by: Nil

Results can also be seen on website https://civil.uet.edu.pk/concrete-laboratory-reports1/

1. * as engraved on the specimens (if any)

2. ** BS3921 requires average of ten clay brick samples for crushing strength and water absorption

3. *** BS5328 requires mean of two cube sample strength at 28 days as characteristic strength

4. **** ACI318-08 requires mean of two sample (6"diax12" cylinder) strength at 28 days as compressive strength

Note: Above results pertain to the unsealed samples supplied to the laboratory

1. The laboratory is not responsible for sampling, originality and construction conditions (such as mix proportion, w/c ratio, compaction, curing and quality of ingredients)

2. The test results are recommended to be interpreted in the light of above factors by the engineer.



Civil Engineering Department

University of Engineering and Technology, Lahore. Pakistan Landline: 042-99029245 & 042-99029202 Mobile: 0307-0496895

6039 Dr. Aqsa

Test Specification

(----)

To: Mr. Qaiser Maqbool Ittefaq Building Solutions Pvt. Ltd.

Project: New Apparel Facility, Ferozwattwan

Our Ref. No. CL/CED/ 3125

Your Ref. No. IBS/SD/ST11

COMPRESSION TEST REPORT



Specimens received on:		09-10-23		-23	Tested on:	10-10-23		in dry/wet condition				ONLINE REPORT
Sr. No.	Mark*	Casting Date*			Size	Wet Weight	Dry Weight	Area of X-Section	Ultimate Ioad	Ultimate Stress	Water Absorpti	Remarks
		DD	ММ	YYYY	(in)	(Kg/ gms)	(Kg/ gms)	(Sq. in)	(Imp.Tons)	(psi)	on (%)	
1	I-Section, Grey, 60mm				2.4" thick		3780	41.82	102	5463		
2	I-Section, Grey, 60mm				2.4" thick		3685	41.82	108	5785		
3	I-Section, Grey, 60mm				2.4" thick		3630	41.82	64	3428		
4	I-Section, Grey, 60mm				2.4" thick		3555	41.82	85	4553		
5	I-Section, Grey, 60mm				2.4" thick	THINE	3630	41.82	81	4339		
6	I-Section, Grey, 60mm				2.4" thick	READ IN	3660	41.82	78	4178		
7						OF THY GORD WHO OREATES	ریجب اندکی خلق ر	133				
8					1							
9								~				
10					<	(A	IOR <u>E</u>					
11												
12												
13												
14												
15												
16												

Dated:

Dated:

10-10-23

09-10-23

Witnessed by: Nil

Results can also be seen on website https://civil.uet.edu.pk/concrete-laboratory-reports1/

1. * as engraved on the specimens (if any)

2. ** BS3921 requires average of ten clay brick samples for crushing strength and water absorption

3. *** BS5328 requires mean of two cube sample strength at 28 days as characteristic strength

4. **** ACI318-08 requires mean of two sample (6"diax12" cylinder) strength at 28 days as compressive strength

Note: Above results pertain to the unsealed samples supplied to the laboratory

1. The laboratory is not responsible for sampling, originality and construction conditions (such as mix proportion, w/c ratio, compaction, curing and quality of ingredients)

2. The test results are recommended to be interpreted in the light of above factors by the engineer.